

GUESSTIMATE OF COST AND RELIABILITY FOR ARCHITECTURE-BASED SOFTWARE

Srinivasa rao.Sabbineni¹, Dr.Rajasekhara Rao.Kurra²

^{1,2} Computer Science and Engineering

¹ K.L.University

² Vaddeswaram

Guntur,India.

Email- Srinu1479cse@kluniversity.in

ABSTARCT:

In architecture-based software system Reliability allocation to components plays major role during the software product design phase, which has close relationship with cost and software modeling. In this paper dynamic programming algorithm is used to allocate the reliability and cost of designing software .we taken minimum step length for allocation reliability to different sizes of components in the system. The result of our research show an optimal solution or near optimal to the problem of choosing the component containing the software can be achieved with lower cost.

Keywords: Architecture-based Software, Software Reliability, Reliability allocation, Dynamic programming, Software development, software model, Reliability Estimation.

1. INTRODUCTION

The Software architecture is composed of components, connectors, and configurations. Any software development has to go to the different phases. In design phase technical lead or system architect will be involving to design the architecture of the application. There are two different types of designs. First one is HLD (high level design) and second one is LLD (low level design).

Software systems have a significant influence on our daily lives. If any HLD or LLD design software failure is happened during operation of software can lead to economic loss and may even cause loss of human lives. That's way unreliable software is not acceptable and should be identified in the starting stage of software development. Later the defects found ,the higher the cost that needs to be paid for them.

The discussion of this paper takes the following structure. Section 2 introduces software reliability allocation model. Section 3 depicts find out the optimal allocation method by using a dynamic programming algorithm. Section 4 illustrates the application of the algorithm proposed in section 3 and section 5 offers conclusion and future work are presented.

2. SOFTWARE RELIABILITY ALLOCATION MODEL

2.1. Software System Development Cost Minimization versus Maximizing Reliability Allocation

In fact, it is difficult to develop the software reliability while releasing the software system development cost because they are two inconsistent constraints. The invented software development cost minimization can be measured from two facts of assessments. One is to find an optimal reliability allocation method while achieving the given reliability such that the development cost can be as small as possible; the other is how to allocate the reliability to each component on the basis of the given cost so that the system reliability can be maximized. This paper focuses on the former one.

Several systems are executed by using a set of interconnected subsystems. Reliability allocation means fixing the reliability among different subsystems so that the total system development cost (including human, material resources, development time and testing time etc) can be minimized. Reliability allocation can be used to planning with such kind of problem that the goal is set prior to the solution. Normally the number of the solution is more than one, as a result reliability allocation is used to deal with the optimal problem with some restrictions.

2.2 Software Reliability And Cost Model

It is reasonable to assume that the cost function fi.

would satisfy these three conditions.

- f_i is a positive definite function
- f_i is non-decreasing.
- f_i increases at a higher rate for higher values of R_i

The third condition suggests that it can be very expensive to achieve the reliability value of 1. According to the definition of software reliability;

$$r(t) = e^{-\lambda t} \text{ -----(1)}$$

where $r(t)$ is continuous-time system reliability, λ is its failure rate.

According to the experience from practical engineering, this paper takes account of the factors by assuming that software reliability and development cost

Satisfy the relations as below:

1). Software development cost is inversely proportional to the number of system failures.

$$E \propto 1/C \text{ -----(2)}$$

$$\lambda \propto E \text{ -----(3)}$$

where C is the development cost and E is the number of system failures. using equation (2), reliability function (1) is therefore

$$C \propto -1/\ln r \text{ -----(4)}$$

2. software development cost is proportional to the complexity and size of the software system.

Taking assumption 2) into account, the equation (4) can be expressed as:

$$C = -\alpha/\ln r \text{ -----(5)}$$

Where α represents the complexity size for developing the software system and is called reliability cost coefficient in this paper.

In consideration of the operation in practical engineering, where personal training, development tools preparation etc. we use character β to represent the basic development cost in this paper.

Reliability cost model as below:

$$C(r) = -\alpha/\ln r + \beta \text{ -----(6)}$$

Equation (6) states the relationship between system development cost and system reliability in our model.

Given a system with many components, the reliability of its component i can be also stated as:

$$C(R_i) = \alpha_i/\ln R_i + \beta_i \text{ -----(7)}$$

2.3 Software reliability model

Here we assume the software system has been designed as an assembly of appropriated connected components. Let there be n components, each with reliability R_i and cost $C_i, i=1,2,\dots,n$. let R_{obj} be the specified target reliability and the total system cost. Let $F(R_1, R_2, \dots, R_n)$ be the function of R and R_i .

The software reliability allocation model can be stated as:

Objective function

$$\text{Min } C \text{ -----(8)}$$

Subject to

$$\{ r = F(r_1, r_2, \dots, r_n) \geq R_{obj}, 0 < r_i < 1 \text{ -----(9)}$$

$$C = \sum C_i = \sum \beta_i \sum \alpha_i / \ln r_i \dots\dots\dots(10)$$

If β is simplified to 0(zero), then eq(10) can be rewriting as:

$$C = \sum C_i = \sum \alpha_i / \ln r_i \dots\dots\dots(11)$$

As for a software system with n sub systems or components within a given architecture ,the development system will increase while enhancing the software reliability target. Significantly ,the greater improvement of the reliability ,the more increase of the cost will be required.

Such a problem can be resolved with variety methods, and dynamic programming is an option.

3. Using Dynamic Programming Algorithm To Solve Reliability Allocation Problem:

A software system with n components and the association function F discussed above is known. The reliability-cost coefficient α of each component and the specified system reliability target R_{obj} is given.

The dynamic programming algorithm is as follows:

Step 1:

Let S represent the reliability matrix $[r_1, r_2, \dots, r_n]$, T represent the cost matrix $[c_1, c_2, \dots, c_n]$, δ be the solving step length, I_i represent the matrix with one column and n rows in which only the value of the i th element is 1 and the rest are all 0. Assume $S_0 = [\max_r, \max_r, \dots, \max_r]$, \max_r represents the maximized possible reliability, for example 0.9999, which means the initial reliability values of the components are all \max_r .

Step 2:

As for S_0, T_0 can be solved(11), C_0 can be given by and system reliability R_0 can be given by function F .

Step 3:

If $R_0 < R_{obj}$ then stop and return. No solutions.

Step 4:

Set Rate=0;

Step 5:

for $i=1$ to n

i) $S' = S_0 - I_i * \delta$;

ii) With regard to S' , Generate reliability R' with the function F , T' with (7), total cost C'

iii) $\Delta C = C_0 - C'$; $\Delta R = R_0 - R'$;

iv) if $R' \geq R_{obj}$ and $\Delta C / \Delta R > \text{Rate}$ then Set Rate= $\Delta C / \Delta R$, $R = R'$, $S = S'$, $C = C'$, $T = T'$;

Step 6:

if $R_0 \neq R$ then set $S_0 = S$; $R_0 = R$; $C_0 = C$; $T_0 = T$;

return to step 4

Where reliability allocation result S_0 is the reliability of each component. R_0 and C_0 are the corresponding system reliability and expected system development cost. T_0 is the expected development cost allocated to each component. Notice from the above that prerequisite to the correctness of the algorithm is that the decrease in reliability of one component can result in that of the whole system and lower the development cost. But that can be guaranteed in our algorithm. The aim of step 5 iv) in the above algorithm is to select an optimal component whose decrease in reliability can result in the maximal cost/reliability variation, which makes the single step programming optimized so that optimal reliability allocation of the ultimate system is guaranteed.

4. Example and Result

Here we choose a system with three independent components r_1, r_2, r_3 . We assume that all the components are essential to the system and their failures are statistically independent. Therefore, the relationship between the total system reliability r and its components' reliability r_i ($i=1, 2, 3$) can be stated as: $r = F(r_1, r_2, r_3) = r_1 * r_2 * r_3$. Suppose that the complexities of the components are 0.45, 0.82 and 0.64 respectively. In order to minimize the system development cost and the system reliability shall be no less than 0.95, how to allocate the reliability to each component. Set the precision of computing is 0.005.

Such a problem can be rewritten as:

$$R = r_1 * r_2 * r_3 \leq 0.95$$

$$C_1 = -0.45 / \ln r_1$$

$$C_2 = -0.82/\ln r_2$$

$$C_3 = -0.64/\ln r_3$$

Compute the values of parameters (r_1, r_2, r_3) with which the total cost C ($C=C_1+C_2+C_3$) is minimized. With respect to each component, we compute the cost with the reliability from 0.95 to 0.995 (increment is 0.005) according to the reliability/cost function model in the data set as shown in Table 1.

According to the algorithm above, set initial state $S_0 = [0.995, 0.995, 0.995]$. Accordingly, $T_0 = [89.77, 163.58, 127.67]$, $\delta=0.005$, and the system cost $C_0=89.77+163.58+127.67=381.02$, system reliability $R_0=0.995*0.995*0.995=0.985$.

Set $i=1, 2, 3$ then compute separately with different value:

1) $S' = S_0 - [0.005, 0, 0] = [0.99, 0.995, 0.995]$, $R'=0.98$, $T' = [44.77, 163.58, 127.67]$, $C'=336.02$ $\Delta C=45$, $\Delta R=0.005$, $\Delta C/\Delta R=9000$.

TABLE 1: COST AND RELIABILITY DATASET

s.n o	r1	c1	r2	c2	r3	c3
1	0.95	8.77	0.95	15.98	0.95	12.47
2	0.955	9.77	0.955	17.80	0.955	13.89
3	0.96	11.02	0.96	20.08	0.96	15.67
4	0.965	12.63	0.965	23.01	0.965	17.96
5	0.97	14.77	0.97	26.92	0.97	21.01
6	0.975	17.77	0.975	32.38	0.975	25.27
7	0.98	22.27	0.98	40.58	0.98	31.67
8	0.985	29.77	0.985	54.25	0.985	42.34
9	0.99	44.77	0.99	81.58	0.99	63.67
10	0.995	89.77	0.995	163.58	0.995	127.67

2) $S' = S_0 - [0, 0.005, 0] = [0.995, 0.99, 0.995]$, $R'=0.98$, $T' = [89.77, 81.58, 127.67]$, $C'=299.02$ $\Delta C=82$, $\Delta R=0.005$, $\Delta C/\Delta R=16400$.

3) $S' = S_0 - [0, 0, 0.005] = [0.995, 0.995, 0.99]$, $R'=0.98$, $T' = [89.77, 163.58, 63.67]$, $C'=317.02$ $\Delta C=64$; $\Delta R=0.005$, $\Delta C/\Delta R=12800$.

Choose the optimal result 1), set $S_0=[0.99, 0.995, 0.995]$, continue to perform the same operation:

1) $S' = S_0 - [0.005, 0, 0] = [0.985, 0.995, 0.995]$, $R'=0.975$, $T' = [29.27, 163.58, 127.67]$, $C'=321.02$, $\Delta C=15$, $\Delta R=0.005$, $\Delta C/\Delta R=3000$

2) $S' = S_0 - [0, 0.005, 0] = [0.99, 0.99, 0.995]$, $R'=0.975$, $T' = [44.77, 81.58, 127.67]$, $C'=254.02$ $\Delta C=82$, $\Delta R=0.005$, $\Delta C/\Delta R=16400$

3) $S' = S_0 - [0, 0, 0.005] = [0.99, 0.995, 0.99]$, $R'=0.975$, $T' = [44.77, 163.58, 63.67]$, $C'=272.02$ $\Delta C=64$; $\Delta R=0.005$, $\Delta C/\Delta R=12800$

Choose the optimal result 2), set $S_0=[0.995, 0.99, 0.995]$, continue to perform the same operation:

1) $S' = S_0 - [0.005, 0, 0] = [0.99, 0.99, 0.995]$, $R'=0.975$, $T' = [44.77, 81.58, 127.67]$, $C'=254.02$, $\Delta C=45$, $\Delta R=0.005$, $\Delta C/\Delta R=9000$

2) $S' = S_0 - [0, 0.005, 0] = [0.995, 0.985, 0.995]$, $R'=0.975$, $T' = [89.77, 54.25, 127.67]$, $C'=271.69$ $\Delta C=27.33$, $\Delta R=0.005$, $\Delta C/\Delta R=5466$

3) $S' = S_0 - [0, 0, 0.005] = [0.995, 0.99, 0.99]$, $R'=0.975$, $T' = [89.77, 81.58, 63.67]$, $C'=235.02$ $\Delta C=64$; $\Delta R=0.005$, $\Delta C/\Delta R=12800$

Choose the optimal result 3), set $S_0=[0.995, 0.995, 0.99]$, continue to perform the same operation:

1) $S' = S_0 - [0.005, 0, 0] = [0.99, 0.995, 0.99]$, $R'=0.975$, $T' = [44.77, 163.58, 63.67]$, $C'=272.02$, $\Delta C=45$, $\Delta R=0.005$, $\Delta C/\Delta R=9000$

2) $S' = S_0 - [0, 0.005, 0] = [0.995, 0.99, 0.99]$, $R'=0.975$, $T' = [89.77, 81.58, 63.67]$, $C'=235.02$ $\Delta C=82$, $\Delta R=0.005$,

$\Delta C/\Delta R=16400$

3) $S' = S_0 - [0, 0, 0.005] = [0.995, 0.995, 0.985]$, $R' = 0.975$, $T' = [89.77, 163.58, 42.34]$, $C' = 295.69$ $\Delta C = 21.33$; $\Delta R = 0.005$, $\Delta C/\Delta R = 4266$

all of the results R' are less than the specified reliability target 0.95. Therefore, the reliability allocation in all cases is as below:

CASE (i):

- 1) System reliability allocation $S_0 = [0.995, 0.995, 0.995]$;
- 2) System reliability $R_0 = 0.985$;
- 3) Expected system development cost $C_0 = 299.02$;
- 4) Expected development cost assigned to each components $T_0 = [89.77, 81.58, 127.67]$.

CASE (ii):

- 1) System reliability allocation $S_0 = [0.99, 0.995, 0.995]$;
- 2) System reliability $R_0 = 0.98$;
- 3) Expected system development cost $C_0 = 254.02$;
- 4) Expected development cost assigned to each components $T_0 = [44.77, 81.58, 127.67]$.

CASE (iii):

- 1) System reliability allocation $S_0 = [0.995, 0.99, 0.995]$;
- 2) System reliability $R_0 = 0.98$;
- 3) Expected system development cost $C_0 = 235.02$;
- 4) Expected development cost assigned to each components $T_0 = [89.27, 81.58, 63.67]$.

CASE (iv):

- 1) System reliability allocation $S_0 = [0.995, 0.995, 0.99]$;
- 2) System reliability $R_0 = 0.98$;
- 3) Expected system development cost $C_0 = 235.02$;
- 4) Expected development cost assigned to each components $T_0 = [89.77, 81.58, 63.67]$.

5. Conclusion

Software reliability allocation to different sizes of system components during software product design phase and implementation phase which has close relationship with software modeling and cost evaluation. We formulated an architecture-based style for showing software reliability optimization problem, on this basis a dynamic programming algorithm has been supported in this paper which can be used to allocate the reliability to every component so as to minimize the cost of designing software system components while meeting the chosen reliability independent. The result of our experiment display an optimal or approximate optimal solution to the problem of selecting the various sizes of components comprising software can be obtained with lower cost (a high reliability). This paper helps to identify the combination or setting the reliabilities to each component maximizing reliability and lower cost. The reliability and cost allocation model presented in this paper can be used to solve the optimal allocation problems in simple and complex systems.

Acknowledgments

I state that in my research work, I am being guided by Dr.K.Rajasekhara Rao Professor, K.L.UNIVERSITY, Vaddeswaram, Guntur, and his guidance and support, I submitting research paper, which is part of research. I also acknowledge the support and encouragement given by my family members and my friends and well-wishers to pursue the Research work

References

- [1] Hui Guan, Tingmei Wang, Weiru Chen "Exploring Architecture-Based Software Reliability Allocation Using a Dynamic Programming Algorithm" Inproc. 2nd symposium Int'l computer science and computational technology, Huangshan, P.R.China, 26-28, Dec .2009, pp.106-109.
- [2] D.L.Parnas. "The Influence of Software Structure on Reliability". In Proc.1975 Int'l Conf. Reliability software, Los Angeles, CA, April 1975. pp. 358-362
- [3] M.L.Shooman. "Structural models for software reliability prediction". In Proc. 2nd Int'l Conf. Software Engineering, San Francisco, CA, October 1976, pp. 268-280..
- [4] M.E. HELANDER, M. Zhao and N. Ohlsson. "Planning Models for Software Reliability and Cost". IEEE Trans. on Software Engineering, 1998, 24(6):420~434
- [5] F. Zahedi and N. Ashrafi, "Software Reliability Allocation Based on Structure, Utility, Price and Cost". IEEE Trans on Software Engineering, 1991, 17 (4):345 - 356
- [6] B. Boehm, R. Valerdi, J A. Lane et al, COCOMO Suite Methodology and Evolution, CrossTalk, 2005, pp. 20 - 25.
- [7] C. Y. Huang, J. H. Lo and S Y. Kuo, "Optimal Allocation of Testing resource Considering Cost, Reliability, and Testing Effort", In Prof. 2004 Pacific Rim Dependable Computing, French Polynesia, 2004, pp.103 - 112.
- [8] S. Y. Kuo, C. Y. Huang and M R. Lyu, "A Framework for Modeling Software Reliability, Using Various Testing Efforts and Fault Detection Rates". IEEE Transactions on Reliability, 2001, 50(3) :310 - 320

- [9] Srinivasarao.Sabbineni, Kurra.Rajasekhara Rao "Assessment of Architecture-based Software System Reliability Allocation on components using a Dynamic programming". IJCA, 2013, 73(19) :41-45
- [10] SrinivasaRao.Sabbineni,RajasekharaRao.Kurra "Estimation of Reliability On Components using a Dynamic Programming". IJCSI, 2013, 10(3) :78-81.
- [11] Srinivasarao.Sabbineni,Dr.Rajasekhaarao.K.Kiran .V.D"Analysis of software reliability and cost assessment relationship for architecture-based software" GJCAT,2011, 1(3) :403-406
- [12] A. Mettas, Reliability allocation and optimization for complex systems. In Proc. Annual Reliability and Maintainability Symposium, Los Angeles, CA, January 2000,pp.216-221
- [13] R. W. Bulter and G.B. Finelli, "The infeasibility of quantifying the reliability of life-critical real-time software", IEEE Trans. on Software Engineering, 1993,19:3-12.
- [14] M.R.Lyu. Handbook of Software Reliability Engineering. IEEE Computer Society Press, New York, 1996, pp.36.
- [15] M. R. Lyu. Handbook of Software Reliability Engineering. IEEE Computer Society Press, New York, 1996, pp.315