

Analysis of Non-Markovian Process by the Inclusion of Supplementary Variables

Shakuntla¹, A.K.Lal², S.S.Bhatia³,

^{1,2,3} *School of Mathematics and Computer Application, T.U. Patiala, Punjab, India*

Abstract- Certain stochastic processes with discrete states in continuous time can be converted into Markov process by the well-known method of including supplementary variables technique. In this paper we developed a mathematical model of the steel industry which manufactures the stainless steel plates and also made an attempt to improve its availability. The failure and repair rates of different subsystem are arbitrary distributed. Lagrange's method for partial differential equations is used to solve system governing equations. Availability analysis of the steel industry helped in identifying the contribution factors and assessing their impact on the system availability.

Key words: Supplementary variable technique, Chapman- Kolmogorov, variable failure and repair rates, Lagrange's method, Runge- Kutta fourth order, MAT-LAB.

1. INTRODUCTION

The study of repairable systems is a basic and important topic in reliability engineering. The system reliability and the system availability play an increasingly important role in power plants, industrial systems, and manufacturing systems. In the earlier studies, a perfect repair model was commonly studied in repairable systems by assuming that the failed system would be repaired as good as new after failures. However in practice, the repairable systems can be brought to one of the possible states following a repair. These states are "as good as new", "as bad as old", "better than old but worse than new", "better than new", and "worse than old" [1].

In the recent past, researcher have recognized to drive more benefits in terms of higher productivity and lower maintenance cost with the application of reliability/availability/maintainability engineering in manufacturing industries. Dayer D. [2] analyzed the unification of reliability/availability/repair-ability models for markovsystem. Kumar D. et al [3] used markovian approach to model the process of feeding system a component of sugar industry for its production improvement. Islamov [3] proposed a general method for determining the reliability of multiple repairable systems. The Kolmogorov equations with a large number of differential equations are transformed into integral differential equation to obtain solutions. Tsai Y. et al [5] presented a method to study the effect of three types of PM actions-mechanical service, repair and replacement on availability of multiple component system. Sharma and Kumar [6] used RAM analysis on a urea production process plant with an aim to minimize its failure ,plant maianebility requirement and optimize

equipment availability. Guo et al [7] applied a more general mathematical model and algorithms for reliability analysis of wind turbines. A three parameter weibull failure rate function is used to model the problem and the parameters are estimated by maximum like hood and least squares. Ke and chu [8] discussed the comparative analysis of availability for a redundant repairable system. Wang et al [9] developed the explicit expression for the mean time to failures, MTTF, and steady state availability for four configuration. Umemura and Dohi [10] analyzed the stochastic behavior of an electronic system through an embedded markov chain approach in continues time and discrete time scale with the purpose to maximize its steady state availability.

In this paper a complex grinding machine of steel industry is discussed. Probability consideration and supplementary variable technique are used in formulation of the problem. Lagrange's method for partial differential equations is used to solve the governing equations. Numerical results based upon true data collected from industry are represented to illustrate the staeady state behavior of the system under different conditions. the result obtained are very informative and can also help in improving the availability of the system.

2. SYSTEM DESCRIPTION, NOTATIONS AND ASSUMPTIONS

2.1.1 Sub-system G (Grinding Machine) : There is one machine subjected to major failure. A grinding machine, often shortened to grinder, is a machine tool used for grinding, which is a type of machining using an abrasive wheel as the cutting tool. Each grain of abrasive on the wheel's surface cuts a small chip from

the work piece via shear deformation. Grinding is used to finish work pieces which must show high surface quality (e.g., low surface roughness) and high accuracy of shape and dimension. As the accuracy in dimensions in grinding is on the order of 0.000025mm, in most applications it tends to be a finishing operation and removes comparatively little metal, about 0.25 to 0.50mm depth. However, there are some roughing applications in which grinding removes high volumes of metal quite rapidly. Thus grinding is a diverse field.

2.1.2 Sub-system D(Descaling Machine): These are two identical machine ($D_i, i = 1, 2$) working in parallel. This sub-system can work with one machine in reduced capacity. Steel Strip Descalesis specifically designed to treat steel strips (carbon, alloy or stainless steel) on a continuous passage under the blast streams at a given speed. The Steel Strip Descales have been developed to treat different strip widths (ranging from 50 to 800 mm for the narrow strips and from 800 to 2100 mm for the large strips), horizontally or vertically positioned. The modular blasting cabinets are conveniently arranged and equipped with a number of wheels in order to achieve the required production rate.

2.1.3 Sub-system G (Hot Steckel Mill): These is five non identical machines connected in series. This subsystem can work in reduced capacity. The classical Steckel mill configuration consists of a rougher with an attached edger that jointly roll out slabs to transfer bar thickness of 25-45mm. Next a four high reversing stand rolls the transfer bar to the desired finished strip thickness in 5-9 passes the strip is coiled after each pass and transported into one of the two Steckelfurnaces arranged on the entry and exit sides. The heat in the furnaces maintains the strip temperature at a high level.

2.1.1 Sub-system C(Cutting Machine): There is one machine can work in reduced capacity. The SM-8 Cutting Machine is designed for in-line cutting of billets, blooms and slabs. This machine is an adaptation of the SM-10 and uses the same tubular and vertical drives. The machine is mounted to a stationary support pad provided by the customer. The product is aligned against fixed stops by the customer, which locates it for the "start of cut" position. Adjustable cut cycle can be provided where a variety of widths are to be cut. Cutting can be done on either hot or cold material (customer must

specify). The machine can be operated remotely if desired.

2.2 Notations

o : The Sub-system/unit is running without any failure.

m : Unit is under preventive maintenance

r : unit is under repair or repair continued.

G^z : indicate the working state of grinding machine w.r.t $z, (z=o, m, r)$.

$H_k^{x,y}$: indicates the working state of the sub-system H_k and H_l w.r.t $x, y, (x, y = o, r) : k = 4, 5, 6, 7 :: l = 3$ if $k = 3, 5, 6, 7$ $l = 4$ if $k = 3, 5, 6, 7; l = 5$ if $k = 2, 3, 5, 6; l = 6$ if $k = 3, 4, 5, 7; ; l = 7$ if $k = 3, 4, 5, 6$.

D_u^t : indicates the working states of the subsystem D the order pair (u^t) and $(3-u^t)$ represents the functioning of the sub-system D w. r. t to "t" and "n" ($u = 1, 2; t = o, r$).

C^z : indicate the working state of grinding machine w.r.t $z, (z=o, g, r)$.

$\alpha_i(y)$: refers failure rate of the sub-system D, H, C and G from normal to failed state ($i = 1, \dots, 8$).

$\delta_1(x)$: refers preventive maintenance rate of the subsystem G and has an elapse repair time repair rate of the sub-system G and has an elapsed repair time 'x'.

σ_1 : refers constant transition state of the subsystem G which transits the system into reduced state.

$\mu_i(x)$: Time dependent repair rates of the subsystem D, H, C and G it from failed to normal state and elapsed repair time $x, (i = 1, \dots, 8)$

$P_1(t)$: The system is working in full capacity.

$P_9(x, t)$: Probability that the system is in state '9' at time t and has an elapsed repair time 'x'.

$P_k(x, y, t)$: Probability that the system is in state k at time t and has an elapsed failure time 'y' and elapsed repair time 'x' ($k = 2, \dots, 8, 10, \dots, 25$).

2.3 Assumption

The assumptions, on which the present analysis is based on, are as follows:

(i) Repair and failure rates are independent of each other.

(ii) Failure and Repair rates of the subsystems are taken as variable.

(iii) Performance wise, a repaired unit is as good as new one for a specified duration.

(iv) Sufficient repair facilities are provided.

(v) System can work at reduced capacity also.

3 MATHEMATICAL MODELING OF THE SYSTEM TRANSIENT STATE

3.1 When both failure and repair rates are variable

Probability consideration gives the following differential difference equations associated with transition diagram.

$$\left[\frac{d}{dt} + A_0 \right] P_1(t) = S_0(t) \quad (1)$$

$$\left[\frac{\partial}{\partial t} + \frac{\partial}{\partial x} + \frac{\partial}{\partial y} + A_1(x, y) \right] P_2(x, y, t) = S_1(x, y, t) \quad (2)$$

$$\left[\frac{\partial}{\partial t} + \frac{\partial}{\partial x} + \frac{\partial}{\partial y} + A_2(x, y) \right] P_3(x, y, t) = S_2(x, y, t) \quad (3)$$

$$\left[\frac{\partial}{\partial t} + \frac{\partial}{\partial x} + \frac{\partial}{\partial y} + A_3(x, y) \right] P_4(x, y, t) = S_3(x, y, t) \quad (4)$$

$$\left[\frac{\partial}{\partial t} + \frac{\partial}{\partial x} + \frac{\partial}{\partial y} + A_4(x, y) \right] P_5(x, y, t) = S_4(x, y, t) \quad (5)$$

$$\left[\frac{\partial}{\partial t} + \frac{\partial}{\partial x} + \frac{\partial}{\partial y} + A_5(x, y) \right] P_6(x, y, t) = S_5(x, y, t) \quad (6)$$

$$\left[\frac{\partial}{\partial t} + \frac{\partial}{\partial x} + \frac{\partial}{\partial y} + A_6(x, y) \right] P_7(x, y, t) = S_6(x, y, t) \quad (7)$$

$$\left[\frac{\partial}{\partial t} + \frac{\partial}{\partial x} + \frac{\partial}{\partial y} + A_7(x, y) \right] P_8(x, y, t) = S_7(x, y, t) \quad (8)$$

$$\left[\frac{\partial}{\partial t} + \frac{\partial}{\partial x} + A_8(x, y) \right] P_9(x, y, t) = S_8(x, y, t) \quad (9)$$

$$\left[\frac{\partial}{\partial t} + \frac{\partial}{\partial x} + \frac{\partial}{\partial y} + T_0(x) \right] P_{10}(x, y, t) = \alpha_1(y) P_9(x, t) \quad (10)$$

$$\left[\frac{\partial}{\partial t} + \frac{\partial}{\partial x} + \frac{\partial}{\partial y} + T_i(x) \right] P_{i+10}(x, y, t) = \alpha_1(y) P_9(x, t) \quad (11)$$

$i = 1 \dots 6$

$$\left[\frac{\partial}{\partial t} + \frac{\partial}{\partial x} + \frac{\partial}{\partial y} + \mu_8(x) \right] P_{17}(x, y, t) = \alpha_8(y) P_1(t) + \sum_{i=1}^7 \mu_i(x) P_{i+17}(x, y, t) \quad (12)$$

$$\left[\frac{\partial}{\partial t} + \frac{\partial}{\partial x} + \frac{\partial}{\partial y} + T_{i+6}(x) \right] P_{i+17}(x, y, t) = \alpha_8(y) P_{i+1}(x, y, t) \quad (13)$$

$i = 1 \dots 7$

$$\left[\frac{\partial}{\partial t} + \frac{\partial}{\partial x} + \frac{\partial}{\partial y} + \mu_1(x) \right] P_{25}(x, y, t) = \alpha_1(y) P_8(x, y, t) \quad (14)$$

Where

$$A_0 = \sum_{i=1}^8 \alpha_i(y) + \sigma_1$$

$$; S_0(t) = \int \mu_8(x) P_{17}(x, y, t) dx dy + \int_{i=1}^7 \mu_i(x) P_{i+17}(x, y, t) dx dy + \delta_{1x} P_9(x, t) dx$$

$$A_1(x, y) = \alpha_8(y) + \mu_1(x) ; S_1(x, y, t) = \alpha_1(y) P_1(t) + \mu_8(x) P_{18}(x, y, t) +$$

$$\delta_1(x)P_{10}(x, y, t)A_2(x, y) = \alpha_8(y) + \mu_2(x) \\ ; S_2(x, y, t) = \\ \alpha_2(y)P_1(t) + \mu_8(x)P_{19}(x, y, t) + \delta_1(x)P_{11}(x, y, t)$$

$$A_3(x, y) = \alpha_8(y) + \mu_3(x) ; S_3(x, y, t) = \\ \alpha_3(y)P_1(t) + \mu_8(x)P_{20}(x, y, t) + \delta_1(x)P_{12}(x, y, t)$$

$$A_4(x, y) = \alpha_8(y) + \mu_4(x) ; S_4(x, y, t) = \\ \alpha_4(y)P_1(t) + \mu_8(x)P_{21}(x, y, t) + \delta_1(x)P_{13}(x, y, t)$$

$$A_5(x, y) = \alpha_8(y) + \mu_5(x) ; S_5(x, y, t) = \\ \alpha_5(y)P_1(t) + \mu_8(x)P_{22}(x, y, t) + \delta_1(x)P_{14}(x, y, t)$$

$$A_6(x, y) = \alpha_8(y) + \mu_6(x) ; S_6(x, y, t) = \\ \alpha_6(y)P_1(t) + \mu_8(x)P_{23}(x, y, t) + \delta_1(x)P_{15}(x, y, t)$$

$$A_7(x, y) = +\alpha_1(y) + \alpha_8(y) + \mu_7(x) \\ ; A_8(x, y) = \sum_{i=1}^7 \alpha_i(y) + \delta_1(x)$$

$$S_7(x, y, t) = \alpha_7(y)P_1(t) + \mu_1(x)P_{25}(x, y, t) + \\ + \mu_8(x)P_{24}(x, y, t) + \delta_1(x)P_{16}(x, y, t)S_8(x, y, t) = \\ \sigma_1P_1(t) + \sum_{i=1}^7 \mu_i(x)P_{i+9}(x, y, t); T_0(x) = \mu_1(x) + \\ \delta_1(x)$$

$$S_9(x, y, t) = \alpha_8(y)P_1(t) + \sum_{i=1}^7 \mu_i(x)P_{i+17}(x, y, t)$$

$$T_i(x) = \mu_{i+1}(x) + \delta_1(x) \quad i = 1 \dots 6 \\ ; T_{i+6}(x) = \mu_i(x) + \mu_8(x) \quad i = 1 \dots 7$$

Boundary Conditions

$$P_{i+1}(0, y, t) = \alpha_i(y)P_1(t) \quad i = 1..7 \\ (15)$$

$$P_9(0, t) = \sigma_1P_1(t) \\ (16)$$

$$P_{i+9}(0, y, t) = \int \alpha_i(y)P_9(x, t)dx \quad i = 1..7 \\ (17)$$

$$P_{17}(0, y, t) = \alpha_8(y)P_1(t) \\ (18)$$

$$P_{i+17}(0, y, t) = \int \alpha_8(y)P_{i+1}(x, y, t)dx \quad i = 1..7 \\ (19)$$

$$P_{25}(0, y, t) = \int \alpha_1(y)P_8(x, y, t)dx \\ (20)$$

Initial Conditions

$$P_1(0) = 1 \\ (21)$$

$$P_9(x, 0) = 0 \\ (22)$$

$$P_i(x, y, 0) = 0 \quad i = 2 \dots 8, 10 \dots 25 \\ (23)$$

The system of differential equations (1-14) together with the boundary conditions (15-20) and initial conditions (21-23) is called Chapman- Kolmogorov differential difference equation. Equation (1) is a linear differential equation of first order and other equations (2) to (14) are linear partial differential equations. In order to find the availability of the system, the governing equations (1-14) will be solved. However, such type of mathematical problems could not be solved analytically so far. An attempt has been made by Gupta (2003) to solve Chapman-Kolmogorov differential equation formulated under the assumption of constant failure rates and variable repair rates by Lagrange's Method. Following the approach of Gupta (2003), equations (2-14) along with the boundary conditions (15-20) have been solved to get probabilities $P_i(t)$ ($i = 1 \dots 25$) for each state:

$$P_1(t) = e^{-A_0t} [1 + \int S_0(t)e^{A_0t} dt] \\ (24)$$

$$P_{i+1}(x, y, t) = e^{-\int A_i(x,y)dx} [\alpha_i(y-x)P_i(t-x) + \\ \int S_i(x, y, t)e^{\int A_i(x,y)dx} dx] \quad i = 1 \dots 7 \\ (25)$$

$$P_9(x, t) = \\ e^{-\int A_8(x,y)dx} [\sigma_1P_1(t-x) + \\ \int S_8(x, y, t)e^{\int A_8(x,y)dx} dx] \\ (26)$$

$$P_{10}(0, y, t) = e^{-\int T_0(x)dx} [\int [\alpha_1(y-x)P_9(x, t-x) \\ + \sigma_1P_1(t-x)] dx] \\ (27)$$

$$P_{i+10}(x, y, t) = e^{-\int T_i(x)dx} [\int [\alpha_1(y-x)P_9(x, t - xe^{T_i x} dx + \alpha_1 y - x P_9(x, t-x) dx]$$

$$i = 1 \dots 6 \quad (28)$$

$$P_{17}(x, y, t) = e^{-\int \mu_8(x)dx} [\alpha_8(y-x)P_1(t-x) + \int S_9(x, y, t) e^{\int \mu_8(x)dx} dx] \quad (29)$$

$$P_{i+17}(x, y, t) = e^{-\int T_i + 6x dx} [\alpha_8(y)P_i + 1x, y, t e^{T_i + 6x dx} + \alpha_8 y - x P_i + 1x, y - x, t - x] dx] \quad (30)$$

$$i = 1 \dots 7$$

$$P_{25}(x, y, t) = e^{-\int \mu_1 x dx} [\alpha_1(y)P_8(x, y, t) e^{\int \mu_1 x dx} + \alpha_1 y - x P_i + 1x, y - x, t - x] dx] \quad (31)$$

From the above relations, all the probabilities are obtained in terms of $P_1(t)$, which is given by the integral equation (1). Thus, the time dependent Availability $A(t)$ of the system is given by

$$A(t) = P_1(t) = e^{-A_0 t} [1 + \int S_0(t) e^{A_0 t} dt] \quad (32)$$

4 SPECIAL CASES

4.1 When both failure and repair rates are constant

If both failure and repair rates are taken as variables. In order to find the availability of the system when both failure and repair rates are constant, system of equations (1-14) reduces to more simplified form which are given below:

$$\left[\frac{d}{dt} + \sum_{i=1}^8 \alpha_i + \sigma_1 \right] P_1(t) = \mu_i P_{i+1}(t) + \delta_1 P_9(t) + \mu_8 P_{17}(t) \quad i=1 \dots 7 \quad (33)$$

$$\left[\frac{d}{dt} + \alpha_8 + \mu_1 \right] P_2(t) = \alpha_1 P_1(t) + \mu_8 P_{18}(t) + \delta_1 P_{10}(t) \quad (34)$$

$$\left[\frac{d}{dt} + \alpha_8 + \mu_2 \right] P_3(t) = \alpha_2 P_1(t) + \mu_8 P_{19}(t) + \delta_1 P_{11}(t) \quad (35)$$

$$\left[\frac{d}{dt} + \alpha_8 + \mu_3 \right] P_4(t) = \alpha_3 P_1(t) + \mu_8 P_{20}(t) + \delta_1 P_{12}(t) \quad (36)$$

$$\left[\frac{d}{dt} + \alpha_8 + \mu_4 \right] P_5(t) = \alpha_4 P_1(t) + \mu_8 P_{21}(t) + \delta_1 P_{13}(t) \quad (37)$$

$$\left[\frac{d}{dt} + \alpha_8 + \mu_5 \right] P_6(t) = \alpha_5 P_1(t) + \mu_8 P_{22}(t) + \delta_1 P_{14}(t) \quad (38)$$

$$\left[\frac{d}{dt} + \alpha_8 + \mu_6 \right] P_7(t) = \alpha_6 P_1(t) + \mu_8 P_{23}(t) + \delta_1 P_{15}(t) \quad (39)$$

$$\left[\frac{d}{dt} + \alpha_1 + \alpha_8 + \mu_7 \right] P_8(t) = \alpha_7 P_1(t) + \mu_1 P_{25}(t) + \mu_8 P_{24}(t) + \delta_1 P_{16}(t) \quad (40)$$

$$\left[\frac{d}{dt} + \sum_{i=1}^7 \alpha_i + \delta_1 \right] P_9(t) = \sigma_1 P_1(t) + \sum_{i=1}^7 \mu_i P_{i+9}(t) \quad (41)$$

$$\left[\frac{d}{dt} + \mu_i + \delta_1 \right] P_{i+9}(t) = \alpha_i P_9(t) \quad i = 1 \dots 7 \quad (42)$$

$$\left[\frac{d}{dt} + \mu_8 \right] P_{17}(t) = \alpha_8 P_1(t) + \sum_{i=1}^7 \mu_i P_{i+17}(t) \quad (43)$$

$$\left[\frac{d}{dt} + \mu_i + \mu_8 \right] P_{i+17}(t) = \alpha_8 P_{i+1}(t) \quad i = 1 \dots 7 \quad (44)$$

$$\left[\frac{d}{dt} + \mu_1 \right] P_{25}(t) = \alpha_1 P_8(t) \quad (45)$$

Initial conditions

$$P_i(0) = \begin{cases} 1, & i = 1 \\ 0, & otherwise \end{cases} \quad (46)$$

Most of the authors have used Laplace transformation and matrix method to solve the availability function. But it is difficult to find Laplace inverse since expression for probability transforms are in very complicated form and the complexity increase with the increase in number of equation. To overcome such type of problems the system of differential equation (33-45) with initial conditions (68) has been solved numerically following the approach earlier used by Gupta et. al. (2007). The numerically computation have been carried out starting from $t = 0$ to $t = 360$ days assuming $t = 0.005$ assuming as one day. Thus the availability of the system when the system running at full capacity under existing condition is given by:

$$A(t) = P_1(t) \tag{47}$$

4.2 Steady State availability with constant Transition Rates:

When $\frac{d}{dt} \rightarrow 0$ and $\frac{\partial}{\partial t} \rightarrow \infty$, $ast \rightarrow \infty$, all transition rates are constant, equations (1-14) takes the form given below:

$$[\sum_{i=1}^8 \alpha_i + \sigma_1]P_1 = \mu_i P_{i+1} + \delta_1 P_9 \quad i=1 \dots 7 \tag{49}$$

$$[\alpha_8 + \mu_1]P_2 = \alpha_1 P_1 + \mu_8 P_{18} + \delta_1 P_{10} \tag{50}$$

$$[\alpha_8 + \mu_2]P_3 = \alpha_2 P_1 + \mu_8 P_{19} + \delta_1 P_{11} \tag{51}$$

$$[\alpha_8 + \mu_3]P_4 = \alpha_3 P_1 + \mu_8 P_{20} + \delta_1 P_{12} \tag{52}$$

$$[\alpha_8 + \mu_4]P_5 = \alpha_4 P_1 + \mu_8 P_{21} + \delta_1 P_{13} \tag{53}$$

$$[\alpha_8 + \mu_5]P_6 = \alpha_5 P_1 + \mu_8 P_{22} + \delta_1 P_{14} \tag{54}$$

$$[\alpha_8 + \mu_6]P_7 = \alpha_6 P_1 + \mu_8 P_{23} + \delta_1 P_{15} \tag{55}$$

$$[\alpha_1 + \alpha_8 + \mu_7]P_8 = \alpha_7 P_1 + \mu_1 P_{25} + \mu_8 P_{24} + \delta_1 P_{16} \tag{56}$$

$$[\sum_{i=1}^7 \alpha_i + \delta_1]P_9 = \sigma_1 P_1 + \sum_{i=1}^7 \mu_i P_{i+9} \tag{57}$$

$$[\mu_i + \delta_1]P_{i+9} = \alpha_i P_9 \quad i = 1 \dots 7 \tag{58}$$

$$[\mu_8]P_{17} = \alpha_8 P_1 + \sum_{i=1}^7 \mu_i P_{i+17} \tag{59}$$

$$[\mu_i + \mu_8]P_{i+17} = \alpha_8 P_{i+1} \quad i = 1 \dots 7 \tag{60}$$

$$\mu_1 P_{25} = \alpha_1 P_8 \tag{61}$$

Solving these equation recursively, we get the long run state probabilities as:

$$P_2 = M_8 P_1$$

$$P_3 = M_7 P_1$$

$$P_4 = M_6 P_1$$

$$P_5 = M_5 P_1$$

$$P_6 = M_4 P_1$$

$$P_7 = M_3 P_1$$

$$P_8 = M_2 P_1$$

$$P_9 = M_1 P_1$$

$$P_{i+9} = \frac{\alpha_i}{K_{15-i}} M_1 P_1 \quad i=1 \dots 7$$

$$P_{17}(t) = \frac{\alpha_8 P_1}{\mu_8} + \sum_{i=1}^7 \mu_i \frac{\alpha_8}{K_{8-i}} P_{i+1}$$

$$P_{18} = \frac{\alpha_8}{K_7} M_8 P_1$$

$$P_{19} = \frac{\alpha_8}{K_6} M_6 P_1$$

$$P_{20} = \frac{\alpha_8}{K_5} M_7 P_1$$

$$P_{21} = \frac{\alpha_8}{K_4} M_5 P_1$$

$$P_{22} = \frac{\alpha_8}{K_3} M_4 P_1$$

$$P_{23} = \frac{\alpha_8}{K_2} M_3 P_1$$

$$P_{24} = \frac{\alpha_8}{K_1} M_2 P_1$$

$$P_{25} = \frac{\alpha_1}{\mu_1} M_2 P_1$$

Where

$$M_1 = \frac{\sigma_1}{K_{15} S_{16}} \quad M_2 = \frac{\frac{\alpha_7 + \delta_1 \alpha_7}{K_{16}} + \frac{\alpha_6}{K_8 K_{16}} M_1}{1 - \frac{\alpha_1}{K_{16}} - \frac{\alpha_8 \mu_8}{\mu_1 K_{16}}}$$

$$M_3 = \frac{\frac{\delta_1 \alpha_6 M_1 + \alpha_6}{K_{17} K_9} + \frac{\alpha_6}{K_{17}}}{1 - \frac{\mu_8 \alpha_8}{K_{17} K_2}}$$

$$M_4 = \frac{\frac{\alpha_5 + \delta_1 \alpha_5}{K_{18}} + \frac{\alpha_5}{K_{18} K_{10}} M_1}{1 - \frac{\mu_8 \alpha_8}{K_3 K_{18}}} \quad M_5 = \frac{\frac{\alpha_4 + \delta_1 \alpha_4}{K_{19}} + \frac{\alpha_4}{K_{19} K_{11}} M_1}{1 - \frac{\mu_8 \alpha_8}{K_4 K_{19}}} \quad M_6 =$$

$$\frac{\frac{\alpha_3 + \delta_1 \alpha_3}{K_{20}} + \frac{\alpha_3 M_1}{K_{12} K_{20}}}{1 - \frac{\mu_8 \alpha_8}{K_5 K_{20}}}$$

$$M_7 = \frac{\frac{\alpha_2 + \alpha_2 \delta_1}{K_{21}} + \frac{\alpha_2 \delta_1}{K_{11} K_{21}} M_1}{1 - \frac{\alpha_8 \mu_8}{K_6 K_{21}}} \quad M_8 = \frac{\frac{\alpha_1 + \alpha_1 \delta_1}{K_{22}} + \frac{\alpha_1 \delta_1}{K_{14} K_{22}} M_1}{1 - \frac{\alpha_8 \mu_8}{K_7 K_{22}}}$$

$$S_{16} = \left(1 - \frac{\sum_{i=1}^7 \mu_i \frac{\alpha_i}{K_{15-i}}}{K_{15}}\right)$$

$$K_{8-i} = \mu_i + \mu_8 \quad i=1...7 \quad K_{15-i} = \mu_i + \delta_1 \quad i=1...7$$

$$K_{15} = \sum_{i=1}^7 \alpha_i + \delta_1 \quad K_{16} = \alpha_1 + \alpha_8 + \mu_7$$

$$K_{17} = \alpha_8 + \mu_6$$

$$K_{18} = \alpha_8 + \mu_5 \quad , K_{19} = \alpha_8 + \mu_4$$

$$K_{20} = \alpha_8 + \mu_3$$

$$K_{21} = \alpha_8 + \mu_2 \quad K_{22} = \alpha_8 + \mu_1$$

Now using normalizing conditions

$$\sum_{i=1}^{25} P_i = 1$$

Once P_0 is determined the probabilities of other states $P_1, P_2, P_3, \dots, P_{25}$ can also be obtained. Finally, we can calculate the availability of the system while running at full capacity under existing condition $A_v = P_1$

(62)

5 NUMERICAL SOLUTIONS

For the above particular cases, the numerical results of availability of the system for transient and long run evaluated as shown in tables 1 to 5

5.1 Transient State Availability

Availability of the system under existing condition i.e. $\alpha_2 = .003, \alpha_3 = .003, \alpha_4 = .005$
 $\alpha_6 = .0004, \alpha_7 = .001, \alpha_5 = .002, \alpha_1 = .009, \delta_1 = .02, \mu_1 = .9, \mu_2 = .03, \mu_3 = .004, \mu_4 = .0001, \mu_5 = .090, \mu_6 = .002, \mu_7 = .006, \mu_8 = .62, \delta_1 = .02$
 $\sigma_1 = .009$

Time In Days	Availability
30	.9697
60	.9691
90	.9677
120	.9634
150	.9521
180	.9410
210	.9261
240	.9091
270	.8921
300	.8739
330	.8642
360	.8630

5.2 Long Run Availability

of the subsystem, the result are shown below in the tables 2 to 5 .

The long run availability of the system as defined in equation (62) has been calculated recursively taking different combinations of the failure and repair rates

Table 2 Effect of transition rates σ_1 and α_8 on availability of the system

σ_1 α_8	0.0090	0.0092	0.0094	0.0096	Transition Rates
0.056	.9436	.9298	.9165	.9036	$\alpha_2 = .003, \alpha_3 = .003, \alpha_4 = .005$ $\alpha_6 = .0004, \alpha_7 = .001, \alpha_5 = .002$ $\alpha_1 = .009, \delta_1 = .02, \mu_1 = .9$ $\mu_2 = .03, \mu_3 = .004, \mu_4 = .008, \mu_5 = .090$ $\mu_6 = .002, \mu_7 = .006, \mu_8 = .62$
0.066	.8710	.8592	.8477	.8367	
0.076	.8099	.7995	.7894	.7797	
0.086	.7616	.7523	.7433	.7347	

Table 3 Effect of transition rates α_1 and α_6 on availability of the system

α_1 α_6	0.0090	0.0092	0.0094	0.0096	Transition Rates
0.0004	.9436	.9298	.9165	.9036	$\alpha_2 = .003, \alpha_3 = .003, \alpha_4 = .005$ $\alpha_8 = .0056, \alpha_7 = .001, \alpha_5 = .002$ $\alpha_1 = .009, \delta_1 = .02, \mu_1 = .9$ $\mu_2 = .03, \mu_3 = .004, \mu_4 = .008, \mu_5 = .090$ $\mu_6 = .002, \mu_7 = .006, \mu_8 = .62, \sigma_1 = .009$
0.0006	.9420	.9282	.9150	.9021	
0.0008	.9404	.9267	.9134	.9006	
0.0010	.9388	.9251	.9119	.8992	

Table 4 Effect of PM rate (δ_1) of the sub system grinding (G) machine on availability

δ_1	0.02	0.04	0.06	0.08
A_v	.9436	.9440	.9501	.9578

Table 5 Effect of PM rate (μ_8) of the sub system grinding (G) machine on availability

μ_8	0.60	0.62	0.64	0.66
A_v	.9423	.9436	.9479	.9623

6. RESULT ANALYSIS

From the tables 1 to 5 we observe that the transition rates of the subsystem D and H affect the availability of the system to run at full capacity. One can see that the result in the table 2 to 5 the failure rate of the subsystem D and H lowers the availability to considerable amount whereas failure rate of the sub system G affect the availability highly. Therefore, the Grinding subsystem is the most critical as far as maintenance is concerned and should be taken on topmost priority.

REFERENCES

- [1] Krivosv, V.V. Recent advances in theory and applications of stochastic point process model in reliability engineering, *Reliab.Eng.Syst.Safe.*92 (2007) 549-551.
- [2] Dayer ,D. Unification of reliability/availability models for markov systems *IEEE Transaction on reliability* 38(1985).
- [3] Kumar, D. Availability of the feeding system in the sugar industry *Micro electron reliability* 28(6) 1988.
- [4] Islamov, R.T. Using markov reliability modeling for multiple repairablesystems. *Reliability engineering and system safety.*1994 113-118.
- [5] Tsai, Y., Wang, K., and Tsai, L., A study of availability centered preventive for multi component system. *Reliability engineering and system safety.*84(2004) 261-270.
- [6] Sharma, R.K. and Kumar, S. Performance modeling in critical engineering system using RAM analysis. *Reliability engineering and system safety.*93(2008)891-897.
- [7] Guo, H., Watson, S., Taver, P. and Xiang, J. Reliability analysis of wind turbines with incomplete failure data collected from the date of intial installation. *Reliability engineering and system safety.*94(2009) 1057-1063.
- [8] Ke, J.C. and Chu, Y.k. Comparative analysis of availability for a redundant repairable system. *AMC*188(2007) 332-338.
- [9] Wang, K.H., Dong, W.L., and Ke, J.B. Comparison of reliability and the availability between four systems with warm stand by components and stand by switching failures. *AMC* 183(2006) 1310-1322.
- [10] Uemura, T. and Dohi, T. Availability analysis of an intrusion tolerant distributed server system with preemitive maintenance, *IEEE Transication on reliability.*59(1) 2010.
- [11] Yuan, Li and Jian, Xu, A deteriorating system with its repairman having multiple vacations. *Applied mathematics and Computation.*217 (2011) 4980-4989.

